



SELFRAG LAB • TECHNICAL SPECIFICATIONS

Design

Self-contained, compact, semi-automated device, designed for installation on level, solid ground in interiors. Constructed in accordance with EU standards.

Outer dimensions

Max. L x W x H	237 x 87 x 206 cm
Clear ceiling height	250 cm
Total weight	2250 kg

Operating conditions

Working temperature	12 - 32 °C
Ambiant conditions when not operating	4 - 40 °C
Humidity max	75%

Required telecommunications infrastructure

For remote customer support a LAN connection is required (internet connection RJ45).

Control, user interface

PLC with graphic touch panel.

User information:

- Process status
- Diagnostic information

Settings

- Voltage (output impulse generator)	90 - 200 kV
- Pulse frequency	1 - 5 Hz
- Working electrode gap	10 - 40 mm

Required utilities

Gas loop:

- Dry Nitrogen (N ₂) Class 4.5	7 bar
--	-------

Electrical energy

- Connection (3-phase, Neutral, Ground - 3L-N-PE)	400V* +/- 10% / 50-60 Hz
---	--------------------------

*Other net voltages can be supplied by using a transformer

Power consumption:

-Peak power consumption	max. 6 kW max. 7 kVA
- Current	max. 10 A
- Standby mode	max. 0.2 kW

Emissions

Sound pressure level (Leq)	
At stand-by	56dB(A)
During processing	79dB(A)
Sound exposure level (LEX)	70dB(A)

For Customer Service contact:

SELFRAG AG • Biberenzelgli 18 • CH-3210 Kerzers • SWITZERLAND
Phone +41 31 750 32 32 • Fax +41 31 750 32 33 • info@selfrag.com • www.selfrag.com

Vers. 04/2012