

SELFRAG
HIGH VOLTAGE PULSE
POWER FRAGMENTATION

PRODUCT SPECIFICATION

SELFRAG LAB • LABORATORY FRAGMENTER




SELFRAG Lab is a laboratory batch equipment. It uses the high voltage pulse power technology of SELFRAG for the selective fragmentation of composite materials, mineralogical, and geological samples in the kilogram range.

For Customer service contact:

SELFRAG AG • Biberenzelgli 18 • CH-3210 Kerzers • SWITZERLAND
Phone +41 31 750 32 32 • Fax +41 31 750 32 33 • info@selfrag.com • www.selfrag.com

Vers. 12 / 2011



SELFRAG LAB • TECHNICAL SPECIFICATIONS

Design

Self-contained, compact, semi-automated device, designed for installation on level, solid ground in interiors. Constructed in accordance with EU standards.

Outer dimensions

Max. L x W x H	237 x 87 x 206 cm
Clear ceiling height	250 cm
Total weight	2250 kg

Operating conditions

Working temperature	12 - 32 °C
Ambiant conditions when not operating	4 - 40 °C
Humidity max	75%

Required telecommunications infrastructure

For remote customer support a LAN connection is required (internet connection RJ45).

Control, user interface

PLC with graphic touch panel.

User information:

- Process status
- Diagnostic information

Settings

- Voltage (output impulse generator)	90 – 200 kV
- Pulse frequency	1 – 5 Hz
- Working electrode gap	10 – 40 mm

Required utilities

Gas loop:

- Dry Nitrogen (N ₂) Class 4.5	7 bar
--	-------

Electrical energy

- Connection (3-phase, Neutral, Ground – 3L-N-PE)	400V*±. 10% / 50-60 Hz
---	------------------------

*Other net voltages can be supplied by using a transformer

Power consumption:

-Peak power consumption	max. 6 kW max. 7 kVA
- Current	max. 10 A
- Standby mode	max. 0.2 kW

For Customer service contact: